

AMENDMENTS TO THE CLAIMS

Please amend the Claims as follows. Insertions are shown underlined while deletions are ~~struck through~~.

1 (currently amended): A liquid injector for injecting a contrast medium into a subject whose fluoroscopic image is to be captured by an imaging diagnostic apparatus, comprising:

a liquid injection mechanism for injecting said contrast medium into said subject;

pattern storing means for registering data of a variable pattern in which an injection rate of the contrast medium for keeping an image contrast of the fluoroscopic image within a predetermined range varies with time, said pattern storing means storing registered data in which the variable pattern is comprised of a linear decrease of the injection rate of the contrast medium from the start of injection to a set point of time, and from said point of time a constant or a linear increase of the injection rate of the contrast medium within a predetermined injection time; and

rate controlling means for varying an operating speed of said liquid injection mechanism ~~with time according to said variable pattern,~~

~~further comprising:~~

~~total amount entering means for accepting entered data of a total amount of the contrast medium to be injected into the subject;~~

~~said rate controlling means comprising means for increasing or reducing said injection rate in elapsed times according to said~~ a modified variable pattern, said modified variable pattern obtained by vertically moving said variable pattern ~~depending on said a~~ total amount of the contrast medium to be injected into the subject.;

~~data entering means for accepting entered data of the body weight of the subject;~~
and

~~total calculating means for increasing or reducing said total amount of the contrast medium to be injected into the subject in proportion to the body weight whose data has been entered by said data entering means,~~

~~wherein waveform of the variable pattern is vertically moved with the~~ said predetermined injection time unchanged, so that the area surrounded by the waveform ~~will be commensurate with the total amount of contrast medium.~~

2 (original): A liquid injector according to claim 1, wherein said pattern storing means comprises means for registering the data of the variable pattern in order to maintain a state in which the image contrast of the fluoroscopic image that is produced by said contrast medium approximates an optimum level.

3 - 4 (canceled)

5 (currently amended): A liquid injector according to claim 1, further comprising:

coefficient storing means for registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;

data entering means for accepting entered data of a region to be imaged of the subject;

coefficient reading means for reading the data of one of the coefficients from said coefficient storing means depending on the region to be imaged of the subject whose data has been entered by said data entering means; and

total calculating means for calculating ~~correcting~~ said total amount of the contrast medium to be injected into the subject ~~by multiplying said total amount by~~ based on the coefficient whose data has been read by said coefficient reading means.

6 (currently amended): A liquid injector according to claim 1, wherein said contrast medium is available in a plurality of types having different concentrations of an effective component contained therein, further comprising:

concentration storing means for registering data of the different concentrations in the types of said contrast medium;

data entering means for accepting entered data of a type of the contrast medium;

concentration reading means for reading data of the concentration from said concentration storing means depending on the type of the contrast medium whose data has been entered by said data entering means; and

total calculating means for calculating ~~increasing or reducing~~ said total amount of the contrast medium to be injected into the subject ~~in inverse proportion to~~ based on said concentration whose data has been read by said concentration reading means.

7 (currently amended): A liquid injector according to claim 1, wherein said contrast medium is available in a plurality of types having different concentrations of an effective component contained therein, further comprising:

concentration storing means for registering data of the different concentrations in the types of said contrast medium;

coefficient storing means for registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;

data entering means for accepting entered data of ~~at least the~~ a body weight of the subject, a region to be imaged of the subject, and one of the types of the contrast medium;

concentration reading means for reading data of the concentration from said concentration storing means depending on the type of the contrast medium whose data has been entered by said data entering means;

coefficient reading means for reading the data of one of the coefficients from said coefficient storing means depending on the region to be imaged of the subject whose data has been entered by said data entering means; and

total calculating means for calculating ~~correcting~~ said total amount of the contrast medium to be injected into the subject, ~~which has been increased or reduced in proportion to~~ based on said body weight obtained by said data entering means, ~~and in inverse proportion to~~ said concentration obtained by said concentration reading means, ~~by multiplying said total amount by~~ and ~~said one of the coefficients obtained by said coefficient reading means.~~

8 (currently amended): A method of injecting a contrast medium into a subject liquid with a liquid injector comprising:

(i) ~~providing a liquid injector comprising:~~

~~— a liquid injection mechanism for injecting a contrast medium into a subject,~~

~~— pattern storing means for registering data of a variable pattern in which an injection rate of the contrast medium for keeping an image contrast of the fluoroscopic image within a predetermined range varies with time, said pattern storing means storing registered data in which the variable pattern is being comprised of a linear decrease of the injection rate of the contrast medium from the start of injection to a set point of time, and~~

from said point of time a constant or a linear increase of the injection rate of the contrast medium within a predetermined injection time; and

~~rate controlling means for varying an operating speed of said liquid injection mechanism with time according to said variable pattern, and~~

(ii) modifying the variable pattern by vertically moving said variable pattern depending on a total amount of the contrast medium to be injected into the subject with said predetermined injection time unchanged; and

(iii) injecting the contrast medium into the subject using the liquid injector at an injection rate of said contrast medium varied with time according to said modified variable pattern by varying an operating speed of a liquid injection mechanism with time;

~~— further comprising:~~

~~— accepting entered data of a total amount of the contrast medium to be injected into the subject;~~

~~— increasing or reducing said injection rate in elapsed times according to said variable pattern depending on said total amount of the contrast medium to be injected into the subject;~~

~~— registering data of the different concentrations in the types of said contrast medium;~~

~~— registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;~~

~~— accepting entered data of at least the body weight of the subject, a region to be imaged of the subject, and one of the types of the contrast medium;~~

~~— reading data of the concentration depending on the type of the contrast medium whose data has been entered;~~

~~— reading the data of one of the coefficients depending on the region to be imaged of the subject whose data has been entered; and~~

~~— correcting said total amount of the contrast medium to be injected into the subject, which has been increased or reduced in proportion to said body weight and in inverse proportion to said concentration, by multiplying said total amount by said one of the coefficients;~~

~~wherein waveform of the variable pattern is vertically moved with the injection time unchanged, so that the area surrounded by the waveform will be commensurate with the total amount of contrast medium.~~

9 - 10 (canceled):

11 (currently amended): A computer unit for controlling operation of a liquid injection mechanism of a liquid injector for injecting a contrast medium into a subject whose fluoroscopic image is to be captured by an imaging diagnostic apparatus, comprising:

pattern storing means for registering data of a variable pattern in which an injection rate of the contrast medium varies with time, said pattern storing means storing registered data in which the variable pattern is comprised of a linear decrease of the injection rate of the contrast medium from the start of injection to a set point of time, and from said point of time a constant or a linear increase of the injection rate of the contrast medium within a predetermined injection time; and

rate controlling means for varying an operating speed of said liquid injection mechanism ~~with time according to said a modified variable pattern, said modified variable pattern obtained by vertically moving said variable pattern depending on a total amount of the contrast medium to be injected into the subject with said predetermined injection time unchanged,~~

~~further comprising:~~

~~total amount entering means for accepting entered data of a total amount of the contrast medium to be injected into the subject;~~

~~said rate controlling means comprising means for increasing or reducing said injection rate in elapsed times according to said variable pattern depending on said total amount of the contrast medium to be injected into the subject,~~

~~concentration storing means for registering data of the different concentrations in the types of said contrast medium;~~

~~coefficient storing means for registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;~~

~~data entering means for accepting entered data of at least the body weight of the subject, a region to be imaged of the subject, and one of the types of the contrast medium;~~

~~concentration reading means for reading data of the concentration from said concentration storing means depending on the type of the contrast medium whose data has been entered by said data entering means;~~

~~coefficient reading means for reading the data of one of the coefficients from said coefficient storing means depending on the region to be imaged of the subject whose data has been entered by said data entering means; and~~

~~total calculating means for correcting said total amount of the contrast medium to be injected into the subject, which has been increased or reduced in proportion to said body weight and in inverse proportion to said concentration, by multiplying said total amount by said one of the coefficients;~~

~~wherein waveform of the variable pattern is vertically moved with the injection time unchanged, so that the area surrounded by the waveform will be commensurate with the total amount of contrast medium.~~

12 - 16 (canceled)

17 (currently amended): ~~An information storage~~A computer readable medium having a program storing stored therein thereon a computer program for executing a computer to perform a method according to claim 814, which is to be read by a computer unit.

18 (new): A liquid injector according to claim 1, further comprising:

data entering means for accepting entered data of a body weight of the subject;
and

total calculating means for calculating said total amount of the contrast medium to be injected into the subject based on said body weight whose data has been entered by said data entering means.

19 (new): A method according to claim 8, further comprising:

registering data of the different concentrations in the types of said contrast medium;

registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;

accepting entered data of a body weight of the subject, a region to be imaged of the subject, and one of the types of the contrast medium;

reading data of the concentration depending on the type of the contrast medium whose data has been entered;

reading the data of one of the coefficients depending on the region to be imaged of the subject whose data has been entered; and

calculating said total amount of the contrast medium to be injected into the subject based on said body weight, said concentration, and said coefficient,

20 (new): A computer unit according to claim 11, wherein said contrast medium is available in a plurality of types having different concentrations of an effective component contained therein, further comprising:

concentration storing means for registering data of the different concentrations in the types of said contrast medium;

coefficient storing means for registering data of predetermined coefficients assigned to respective regions to be imaged of the subject;

data entering means for accepting entered data of a body weight of the subject, a region to be imaged of the subject, and one of the types of the contrast medium;

concentration reading means for reading data of the concentration from said concentration storing means depending on the type of the contrast medium whose data has been entered by said data entering means;

coefficient reading means for reading the data of one of the coefficients from said coefficient storing means depending on the region to be imaged of the subject whose data has been entered by said data entering means; and

total calculating means for calculating said total amount of the contrast medium to be injected into the subject based on said body weight whose data has been entered by said data entering means, said concentration whose data has been read by said concentration reading means, and said coefficient whose data has been read by said coefficient reading means.

21 (new): A computer readable medium having a program stored thereon for executing a computer to perform a method according to claim 19.